



SUPRA 950 U



*All the advantages of SUPRA in a new undermount unit.
For large-sized trucks.*

The new **SUPRA 950 U** is an extremely powerful, yet quiet, undermount diesel truck unit that combines exceptional cooling capacities with robust reliability.

The ideal solution for vehicles with high cabs or trucks with draw-bar drailers, SUPRA 950 U can also be adapted onto city-trailers up to 90m³.

Also available as SUPRA 950 U Mt° for multi-temperature applications.

▶ **Highly resistant to humidity, pollution and dust** meaning you can carry out your business in complete confidence

▶ **Exceptional reliability and performance** that ensures you enhanced product protection and low operation costs

▶ **Low-noise operation** so that you can operate at all hours even in noise-sensitive areas

▶ **User-friendly EasyCOLD® microprocessor control** for a unit that is simple to operate

▶ **A new generation extra-flat evaporator** to give you optimized loading capacity.



■ **Condensor**

Dimensions: 1860 x 823 x 631 mm

Weight: 553 kg

■ **Refrigeration capacity**

Road

0°C: 10 700 W
- 20°C: 6 300 W

Standby

0°C: 8 500 W
- 20°C: 5 500 W

Ambient temperature at + 30°C
(per ATP procedure)

■ **Airflow**

2925 m³/h (constant at high & low speed)



■ **Evaporator**

Dimensions: 1 450 x 752 x 219 mm

Weight: 52 kg

T model

- HFC R404A refrigerant
- 1-1 litre Tri-Vortex diesel engine
- 05G 6-cylinder compressor
- Standby motor
- Remote plug
- Low-noise sound control kit
- Automatic hot gas heating and defrost system
- Manual defrost
- Directly accessible oil & coolant gauges
- Two sight glasses to monitor refrigerant level
- Dry air, fuel and remote oil filters
- Pre-installed accessory package (electric fuel pump, fuel lines, battery cables)
- EasyCOLD® Microprocessor control system:
 - Automatic Start/Stop
 - Visual displays for: cooling - heating - defrost - auto-start - temperature
 - Programmable defrost interval
 - Battery voltage indicator
 - Automatic diesel restart
 - Cab command with: Automatic pre-trip unit check function - Back-lit cab command display and keys to set and programme the microprocessor parameters

Safety devices

- Standby motor overload protection
- Standby motor short cycle protection
- High coolant temperature protection
- Low engine oil protection
- Low and high refrigerant pressure protection
- Receiver tank pressure relief valve

S model

Version without low-noise sound control kit

Accessories

- Supply air sensor to avoid top freezing
- Battery
- Battery box
- Fuel tank 90 or 200 l
- Automatic phase reverser
- Fuel heater
- Single compartment control panel & cable extension
- External watertight box for cab command

New Zealand
Transcold Group
38 Oakleigh Avenue
Takanini, Auckland
Ph: (09) 269 0660
Fax: (09) 269 0661

Perth
TRACS
3 Tipping Road
Kewdale WA 6105
Ph: (08) 9353 4544
Fax: (08) 9353 4467

Adelaide
RTS Refrigeration
17 Streiff Road
Wingfield SA 5013
Ph: (08) 8262 6535
Fax: (08) 8349 5166

Melbourne
Carrier Transcold
58 Calaroo Drive
Derrimut VIC 3030
Ph: (03) 8353 6100
Fax: (03) 8353 6140

Brisbane
Carrier Transcold
57 Grindle Road
Rocklea QLD 4106
Ph: (07) 3276 7433
Fax: (07) 3272 9500

Sydney
Carrier Transcold
3 - 5 Hill Road
Homebush Bay NSW 2141
Ph: (02) 9648 6100
Fax: (02) 9648 6101



Carrier

A United Technologies Company

Carrier Transcold Australia
National Sales: 1300 130 276
24hr Service: 1800 448 166

